## Bolfresh®

### BCB

### Controlled breathing polyolefin film

- Optimum shrinkage on odd-shaped items
- Strong seal and good machinability
- Controlled breathing rate
- Delivered under polyethylene sleeve with plastic winding core






#### **APPLICATIONS**

**Bolfresh® BCB** film is designed for wrapping irregular shaped food products which require good shrinkage properties.

Its unique formulation allows fast shrinking at low temperatures and thereby prevents heat exposure damage when packing products like portions of cheese.





**Bolfresh® BCB**'s permeability optimizes the cheese breathing and thus extends its shelf life.

# Bolfresh BCB



OPTIMUM SHRINKAGE



70 60 Standard 50 shrink film Free shrink (%) 40 30 20 10 0 100°C Temperature

To the Bolfresh® outstanding performance can be added Bolloré's secured manufacturing and quality standards:



#### **FOOD CONTACT COMPLIANCE**

This Bolloré film complies with the applicable EC and USA regulations. Full details (with the conditions of use) are given on the Declaration

of Compliance for food contact (this document is available on request).



#### **CERTIFICATIONS**

Bolloré facility manufactures the packaging films according to the food safety standard BRC/IOP (British Retail Consortium, Institute of Packaging), as well as ISO 22000.



#### **TRACEABILITY**

Bolloré ensures the traceability of the materials and items manufactured at all production stages, including raw material, production and shipment.

The technical features of the products defined herein are given for typical values. They are guides for the use of the quoted films and are not for use as limiting specification.

Users have to ensue that they are suitable for specific applications as performance may vary with processing conditions.

Properties and performance are subjet to change and Bolloré keeps the right to modify the definition and properties of its products without prior notice

#### **TECHNICAL FEATURES**

	12 microns	15 microns	19 microns
Gloss (%)		118	
Haze (%)		2,5	
Shrinkage (%) at 93°C at 120°C	30 70		
Seal strength (N/30 mm) at 160°C at 190°C	24 48	27 60	35 65
Water steam permeability (g/m²/24h at 38°C - 100% RH)	37	28	24
O <sub>2</sub> permeability (cm³/m²/24h bar at 23°C 0% RH)	13 000	9 800	8 400
CO <sub>2</sub> permeability (cm³/m²/24h bar at 23°C 0% RH)	52 000	38 500	33 000
Roll length (m)	3 500	2 670	2 140
Internal diameter (mm)	76,2		
External diameter (mm)	245		

#### **PRESENTATION**

**Bolfresh® BCB** exists in Singlewound version only (BCB-S).

> For more information, please contact our sales department.

