# Bolfresh®

## BTS

### High sealing performance shrinkfilm

- Excellent heatsealing characteristics
- Secure package at low temperatures
- Good optics
- Stiffness improving machinability at very high speed






### **APPLICATIONS**

**Bolfresh® BTS** belongs to the range of specialized films dedicated to high speed HFFS machines.





## Bolfresh BTS



To the Bolfresh® outstanding performance can be added Bolloré's secured manufacturing and quality standards:



#### **FOOD CONTACT COMPLIANCE**

This Bolloré film complies with the applicable EC and USA regulations.

Full details (with the conditions of use) are given on the Declaration of Compliance for food contact (this document is available on request).



#### **CERTIFICATIONS**

Bolloré facility manufactures the packaging films according to the food safety standard BRC/IOP (British Retail Consortium, Institute of Packaging), as well as ISO 22000.



#### TRACEABILITY

Bolloré ensures the traceability of the materials and items manufactured at all production stages, including raw material, production and shipment.

### SEALING PERFORMANCE

The unique combination of rigid layers at the core and sealable external layers means high performance in sealing at high speed.

#### **TECHNICAL FEATURES**


	14 microns	
Gloss (%)	115	
Haze (%)	2	
Shrinkage (%) at 120°C	30 /	
Roll length (m)	3 330	
Internal diameter (mm)	76,2	
External diameter (mm)	280	

#### **PRÉSENTATION**

Bolfresh® BTS is available in Singlewound version: BTS-S.



> For more information, please contact our sales department.



Users have to ensue that they are suitable for specific applications as performance may vary with processing conditions.

Properties and performance are subjet to change and Bolloré keeps the right to modify the definition and properties of its products without prior notice

